

Accessories for drum and container pumps



PVC-hose

crystal clear with fabric lining, suitable for non flammable, neutral and aggressive media

Operating pressure: 10 bar*

Temperature: -35 °C up to +60 °C*

1/2" **9049**
3/4" **9050**



Universal chemical- and solvent hose, conductive

inner wall homogeneous, smooth, EPDM (Ethylene Propylene Rubber) conductive, suitable for many alkalies, acids, acetates, aldehydes, amines, esters, ethers and ketones, not suitable for carbonic gassy products and their derivatives, as well as oils and gasoline

Operating pressure: 16 bar*

Temperature: -40 °C up to +90 °C*

1/2" **9054**
3/4" **9055**



Multi purpose chemical hose, conductive

inner wall homogeneous, smooth, PE-X (knitted polyethylene), conductive, suitable for nearly all chemicals.

Not suitable for oleum, brom and chlorsulfon acid

Operating pressure: 10 bar*

Temperature: -25 °C up to +90 °C*

1/2" **9059**
3/4" **9060**



PVC-hose

crystal clear with fabric lining, suitable for non flammable, neutral and aggressive media.

Operating pressure: 10 bar

Medium temperature: -35 °C up to +60 °C

3/4" **9050**
1" **9051**
1 1/4" **9052**
1 1/2" **9053**



Universal chemical- and solvent hose, conductive

inner wall homogeneous, smooth, EPDM (Ethylene Propylene-Rubber) conductive, suitable for many alkalies, acids, acetates, aldehydes, amines, esters, ethers and ketones, not suitable for carbonic gassy products and their derivatives as well as for oils and gasoline.

Operating pressure: 16 bar

Temperature: -40 °C up to +90 °C

3/4" **9055**
1" **9056**
1 1/4" **9057**
1 1/2" **9058**



Multi purpose chemical hose, conductive

inner wall homogeneous, smooth, PE-X (knitted polyethylene), conductive, suitable for nearly all chemicals.

Not suitable for oleum, brom and chlorsulfon acide

Operating pressure: 10 bar

Temperature: -25 °C bis +90 °C

(also available in a food grade version)

3/4" **9060**
1" **9061**
1 1/4" **9062**
1 1/2" **9063**



Mineral oil hose

PN10 with fabric lining

PN10 with fabric lining

PN16 TW-hose

PN16 TW-hose

3/4" **9065**
1" **9066**
1 1/4" **9067**
1 1/2" **9068**



Rubber hose food grade BUTYL/BUTYL

suitable for animal and vegetable fat and oils, milk products, mineral water, fruit juice and alcohol up to 92%

Temperature: up to 120 °C

3/4" **9069a**
1" **9069**

AG: male thread